

ECOLEC Retail Price List

Tel: 01902 457575 Fax: 01902 457797



Wireless Heating Systems

SPACE SAVING VERTICAL RADIANT PANEL WITHOUT VENTS (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
1.1	ECO 2000D/RP/PC/RX/V	500 x 2000 x 40	2000	1600	5459	337.00
1.2	ECO 1500D/RP/PC/RX/V	500 x 1500 x 40	1500	1200	4094	289.00
1.3	ECO 1000D/RP/PC/RX/V	500 x 1000 x 40	1000	800	2729	249.00
1.4	ECO 750D/RP/PC/RX/V	500 x 750 x 40	750	600	2047	187.00
1.5	ECO 500D/RP/PC/RX	500 x 500 x 40	500	400	1365	149.00
1.6	ECO 1000D/SB/RP/PC/RX/V	250 x 2000 x 40	1000	800	2729	267.00
1.7	ECO 750D/SB/RP/PC/RX/V	250 x 1500 x 40	750	600	2047	247.00
1.8	ECO 500D/SB/RP/PC/RX/V	250 x 1000 x 40	500	400	1365	197.00
Brushed Stainless Steel						
2.1	ECO 1000DLL/RP/SS/RX/V	500 x 2000 x 40	1000	980	3343	397.00
2.2	ECO 1000DL/RP/SS/RX/V	500 x 1500 x 40	1000	735	2507	347.00
2.3	ECO 500DLL/RP/SS/RX/V	500 x 1000 x 40	500	490	1671	275.00
2.4	ECO 500DL/RP/SS/RX/V	500 x 750 x 40	500	373	1272	240.00
2.5	ECO 250DLL/RP/SS/RX	500 x 500 x 40	250	247	842	200.00
2.6	ECO 500DLL/SB/RP/SS/RX/V	250 x 2000 x 40	500	490	1671	280.00
2.7	ECO 500DL/SB/RP/SS/RX/V	250 x 1500 x 40	500	373	1272	260.00
2.8	ECO 250DLL/SB/RP/SS/RX/V	250 x 1000 x 40	250	247	842	240.00
Stainless Mirror						
3.1	ECO 1000DLL/RP/MF/RX/V	500 x 2000 x 40	1000	680	2194	480.00
3.2	ECO 1000DL/RP/MF/RX/V	500 x 1500 x 40	1000	500	1706	420.00
3.3	ECO 500DLL/RP/MF/RX/V	500 x 1000 x 40	500	336	1146	360.00
3.4	ECO 500DL/SB/RP/MF/RX/V	500 x 750 x 40	500	250	853	330.00
3.5	ECO 250DLL/RP/MF/RX	500 x 500 x 40	250	170	580	300.00
3.6	ECO 500DLL/SB/RP/MF/RX/V	250 x 2000 x 40	500	336	1146	390.00
3.7	ECO 500DL/SB/RP/MF/RX/V	250 x 1500 x 40	500	250	853	360.00
3.8	ECO 250DLL/SB/RP/MF/RX/V	250 x 1000 x 40	250	170	580	330.00

ALSO AVAILABLE IN HORIZONTAL FORMAT, WHEN ORDERING SIMPLY CHANGE THE LAST LETTER OF THE MODEL FROM 'V'

CHROME FINISH BATHROOM LADDER TOWEL RAIL

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
4.1	ELTR 50/82	500 x 820 X 80	300	300	1023	220.00
4.2	ELTR 60/118	600 x 1180 X 80	600	600	2047	260.00

DIGITAL THERMOSTATIC CONTROL ELEMENT INCLUDED - DOES NOT WORK WITH REMOTE CONTROL SYSTEM

SPACE SAVING VERTICAL IP44 GLASS RADIATOR - Ebony Black Gloss

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
5.1	ECO 500D/IP44/GR/RX/V	500 x 500 x 40	500	300	1023	590.00
5.2	ECO 500DL/IP44/GR/RX/V	500 x 750 x 40	750	450	1535	634.00
5.3	ECO 1000D/IP44/GR/RX/V	500 x 1000 x 40	1000	600	2047	678.00
5.4	ECO 1500D/IP44/GR/RX/V	500 x 1500 x 40	1500	900	3070	766.00
5.5	ECO 500D/SB/IP44/GR/RX/V	250 x 1000 x 40	500	300	1023	678.00
5.6	ECO 750D/SB/IP44/GR/RX/V	250 x 1500 x 40	750	450	1535	722.00
5.7	ECO 1000D/SB/IP44/GR/RX/V	250 x 2000 x 40	1000	600	2047	737.00

ALL RAL COLOURS ARE AVAILABLE. PLEASE PHONE FOR A QUOTATION.

SPACE SAVING VERTICAL IP44 MIRROR RADIATOR - Silver

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
6.1	ECO 500D/IP44/MR/RX/V	500 x 500 x 40	500	300	1023	503.00
6.2	ECO 500DL/IP44/MR/RX/V	500 x 750 x 40	750	450	1535	546.00
6.3	ECO 1000D/IP44/MR/RX/V	500 x 1000 x 40	1000	600	2047	590.00
6.4	ECO 1500D/IP44/MR/RX/V	500 x 1500 x 40	1500	900	3070	693.00
6.5	ECO 500D/SB/IP44/MR/RX/V	250 x 1000 x 40	500	300	1023	590.00
6.6	ECO 750D/SB/IP44/MR/RX/V	250 x 1500 x 40	750	450	1535	634.00
6.7	ECO 1000D/SB/IP44/MR/RX/V	250 x 2000 x 40	1000	600	2047	649.00

SPACE SAVING VERTICAL IP44 MyPICTURE RADIATOR

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
7.1	ECO 1500D/IP44/MP/RX/V	500 x 1500 x 35	1500	1100	3753	540.00

PLEASE SEND A SUITABLE HIGH RESOLUTION JPEG IMAGE FOR PRINTING

SPACE SAVING VERTICAL IP44 BATHROOM PANEL (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
8.1	ECO 1000/IP44/PC/RX/V	500 x 2000 x 40	1000	800	2388	317.00
8.2	ECO 750/IP44/PC/RX/V	500 x 1500 x 40	750	600	1876	267.00
8.3	ECO 500/IP44/PC/RX/V	500 x 1000 x 40	500	400	1279	227.00
8.4	ECO 250/IP44/PC/RX	500 x 500 x 40	250	200	682	149.00
8.5	ECO 2546/IP44/PC/RX/V	400 x 600 x 40	250	200	682	139.00
8.6	ECO 546/IP44/PC/RX/V	400 x 600 x 40	500	400	1364	149.00
8.7	ECO 500D/SB/RP/PC/RX/V	250 x 1000 x 40	500	350	1194	197.00
8.8	ECO 750D/SB/RP/PC/RX/V	250 x 1500 x 40	750	550	1876	247.00
8.9	ECO 1000D/SB/RP/PC/RX/V	250 x 2000 x 40	1000	700	3753	267.00
Brushed Stainless Steel						
9.1	ECO 1000/IP44/SS/RX/V	500 x 2000 x 40	1000	800	2388	427.00
9.2	ECO 750/IP44/SS/RX/V	500 x 1500 x 40	750	600	1876	327.00
9.3	ECO 500/IP44/SS/RX/V	500 x 1000 x 40	500	400	1279	277.00
9.4	ECO 250/IP44/SS/RX/V	500 x 500 x 40	250	200	682	207.00
9.5	ECO 2546/IP44/SS/RX/V	400 x 600 x 40	250	200	682	200.00
9.6	ECO 546/IP44/SS/RX/V	400 x 600 x 40	500	400	1364	177.00
9.7	ECO 500D/SB/IP44/SS/RX/V	250 x 1000 x 40	500	350	1194	240.00
9.8	ECO 750D/SB/IP44/SS/RX/V	250 x 1500 x 40	750	550	1876	260.00
9.9	ECO 1000D/SB/IP44/SS/RX/V	250 x 2000 x 40	1000	700	3753	280.00
Accessories						
10.1	TR3 - 3 Chrome or Satin Stainless Steel Towel Rails					45.00
10.2	TR2 - 2 Chrome or Satin Stainless Steel Towel Rails					30.00
10.3	TR1 - 1 Chrome or Satin Stainless Steel Towel Rails					15.00
10.4	TR1 or TR2					15.00 / 30.00

EACH TOWEL RAIL INCLUDES 2 CHROME PLATED BRACKETS

SPACE SAVING CORNER IP44 BATHROOM PANEL (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
11.1	ECO 600/CU/RP/PC/RX/V	400 x 1000 x 40	750	600	2047	195.00
11.2	ECO 800/CU/RP/PC/RX/V	320 x 1800 x 40	1000	800	2729	295.00
Brushed Stainless Steel						
12.1	ECO 600/CU/RP/SS/RX/V	400 x 1000 x 40	500	450	1535	297.00
12.2	ECO 800/CU/RP/SS/RX/V	320 x 1800 x 40	750	650	2217	397.00
Stainless Mirror						
13.1	ECO 600/CU/RP/MR/RX/V	400 x 1000 x 40	500	315	1074	387.00
13.2	ECO 800/CU/RP/MR/RX/V	320 x 1800 x 40	750	455	1552	487.00

SPACE SAVING HORIZONTAL RADIANT PANEL CONVECTOR WITH VENTS (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Brushed Stainless Steel						
14.1	ECO 2000D/RC/SS/RX/H	2000 x 500 x 40	2000	1600	5459	397.00
14.2	ECO 1500D/RC/SS/RX/H	1500 x 500 x 40	1500	1200	4094	347.00
14.3	ECO 1000D/RC/SS/RX/H	1000 x 500 x 40	1000	800	2729	275.00

SPACE SAVING RADIANT CARAVAN PANEL (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
15.1	ECO 250D/RP/PC/RX	500 x 500 x 40	250	200	682	129.00
15.2	ECO 500D/RP/PC/RX	500 x 500 x 40	500	400	1365	149.00
15.3	ECO 750D/RP/PC/RX/V	500 x 750 x 40	750	600	2047	177.00

RADIATORS FOR 'SPECIAL NEEDS'

SPACE SAVING VERTICAL IP44 43°C RADIANT HEALTHCARE PANEL (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
16.1	ECO 1000DLL/IP44/PC/RX/43/V	500 x 2000 x 40	1000	590	2013	317.00
16.2	ECO 1000DL/IP44/PC/RX/43/V	500 x 1500 x 40	1000	443	1511	267.00
16.3	ECO 500DLL/IP44/PC/RX/43/V	500 x 1000 x 40	500	295	1006	227.00
16.4	ECO 500DL/IP44/PC/RX/43/V	500 x 750 x 40	500	222	757	177.00
16.5	ECO 250DLL/IP44/PC/RX/43	500 x 500 x 40	250	148	505	149.00
16.6	ECO 250DLL/SB/IP44/PC/RX/43/V	250 x 1000 x 40	250	148	505	197.00
16.7	ECO 500DL/SB/IP44/PC/RX/43/V	250 x 1500 x 40	500	222	757	247.00
16.8	ECO 500DLL/SB/IP44/PC/RX/43/V	250 x 2000 x 40	500	295	1006	267.00

SPACE SAVING VERTICAL IP44 55°C RADIANT SCHOOL PANEL (DEPTH 40mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
17.1	ECO 1000DLL/IP44/PC/RX/55/V	500 x 2000 x 40	1000	860	2934	317.00
17.2	ECO 1000DL/IP44/PC/RX/55/V	500 x 1500 x 40	1000	642	2190	267.00
17.3	ECO 500DLL/IP44/PC/RX/55/V	500 x 1000 x 40	500	425	1450	227.00
17.4	ECO 500DL/IP44/PC/RX/55/V	500 x 750 x 40	500	321	1095	177.00
17.5	ECO 250DLL/IP44/PC/RX/55	500 x 500 x 40	250	214	730	149.00
17.6	ECO 250DLL/SB/IP44/PC/RX/55/V	250 x 1000 x 40	250	214	730	197.00
17.7	ECO 500DL/SB/IP44/PC/RX/55/V	250 x 1500 x 40	500	321	1095	247.00
17.8	ECO 500DLL/SB/IP44/PC/RX/55/V	250 x 2000 x 40	500	425	1450	267.00

COMPACT CONSERVATORY FAN HEATER (DEPTH 80mm) WORKS WITH WCT 100/TX CONTROLLER

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
18.1	LST 2000/C/60/WM/PC/RX	600 x 300 x 80	2000	2000	6824	179.00
18.2	LST 1500/C/60/WM/PC/RX	600 x 300 x 80	1500	1500	5118	175.00
Brushed Stainless Steel						
19.1	LST 2000/C/60/WM/SS/RX	600 x 300 x 80	2000	2000	6824	199.00
19.2	LST 1500/C/60/WM/SS/RX	600 x 300 x 80	1500	1500	5118	195.00
Stainless Mirror						
20.1	LST 2000/C/60/WM/MF/RX	600 x 300 x 80	2000	2000	6824	279.00
20.2	LST 1500/C/60/WM/MF/RX	600 x 300 x 80	1500	1500	5118	275.00

COMPACT LST 43°C FAN HEATER (DEPTH 80mm) WORKS WITH WCT 100/TX CONTROLLER

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
21.1	LST 1000/C/43/WM/PC/RX	600 x 300 x 80	1000	1000	3412	172.00
Brushed Stainless Steel						
22.1	LST 1000/C/43/WM/SS/RX	600 x 300 x 80	1000	1000	3412	192.00
Stainless Mirror						
23.1	LST 1000/C/43/WM/MF/RX	600 x 300 x 80	1000	1000	3412	272.00

HEALTHCARE LST 43°C FAN HEATER (DEPTH 80mm) WORKS WITH WCT 100/TX CONTROLLER

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
24.1	LSTH 2000/43/PC/RX	1000 x 200 x 190	2000	2000	6824	250.00
Brushed Stainless Steel						
25.1	LSTH 2000/43/SS/RX	1000 x 200 x 190	2000	2000	6824	300.00
Stainless Mirror						
26.1	LSTH 2000/43/MF/RX	1000 x 200 x 190	2000	2000	6824	380.00

KICK SPACE HEATER

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Brushed Stainless Steel						
27.1	KS 2000/SS/RX	360 x 90 x 260	2000	2000	6824	161.00

CEILING HEATER (DEPTH 35mm)

Line Ref.	Code	Dimensions (w x h x d)	Element (Watts)	Output (Watts)	Output (BTU's)	Retail
Powder Coated White						
28.1	ECO 300/70/FF/FP/PC/RX	595 x 595 x 35	300	200	682	160.00
28.2	ECO 600/70/FF/FP/PC/RX	1195 x 595 x 35	600	400	1364	210.00
28.3	ECO 300/70/SM/FP/PC/RX	600 x 600 x 35	300	200	682	160.00
28.4	ECO 600/70/SM/FP/PC/RX	1200 x 600 x 35	750	600	2047	210.00

CONTROLLERS

Line Ref.		Model	Sensor	Power	Retail
29.1	REMOTE THERMOSTAT/TIMER	WCT 100/TX	AIR	BATTERY	99.00
29.2	TOUCH THERMOSTAT	WCT 200/TX	MOVEMENT	BATTERY	99.00
29.3	LANDLORD CONTROL	WCT 300/TX	AIR	BATTERY	125.00
29.4	MAKE-UP MIRROR/LIGHT CONTROL	WCT 400/TX	DIMMER	BATTERY	125.00
29.5	OPCC - OFF-PEAK CHANGEOVER CONTACTOR	ECO 7000	-	MAINS	160.00

NB. WE CAN SUPPLY YOU WITH A CIRCUIT DRAWING TO USE WITH ECONOMY 7

CARRIAGE CHARGES NOT INCLUDED - ALL PRICES INCLUDE 17.5% VAT

BESPOKE & SPECIAL NEEDS HEATERS AVAILABLE.
PLEASE PHONE FOR A QUOTE

WHEN DELIVERY IS MADE ON PALLETS, IT IS UP TO THE CUSTOMER
TO UNLOAD AS THE DRIVER IS NOT CONTRACTED FOR THIS PURPOSE.
ALL DELIVERIES ARE MADE TO THE GROUND FLOOR.

Please consult your local NICEIC Electrician
CONNECT HEATERS TO A FUSED SPUR
- BEST PRACTICE

NON IP44 HEATERS CAN BE FITTED
WITH A 13AMP PLUG

Sharrocks Street, Wolverhampton WV1 3RP

Tel: **01902 457575** Fax: **01902 457797** Email: **sales@ecolec.co.uk** Website: **www.ecolec.co.uk**